

# granite cutting bearing steel grit

## Specifications :

Price	Contact Us
Place of Origin	Shandong, China
Payment Terms	T/T, L/C, Western Union, etc.
Delivery Detail	10-25 Working Days.
Keyword	Steel Angular Grit

## Detail Introduction :

### Bearing steel grit

Bearing steel grit is made of chrome alloy material which are fast atomized after melting. After heat treatment, it is featured with optimum mechanical characteristics, good tenacity, high fatigue resistance, long working-life, low consumption and so on. 30% will be saved.

### Specifications

Product Name	Chemical Composition	
Chemical Composition	C	0.701.20%
	Cr	1.0-1.50%
	Mn	0.61.20%
	Si	0.401.20%
	S	?0.05%
	P	?0.05%
Micro Hardness	GP:4250HRC (399509HV) GL:5660HRC (620713HV) GH:6366HRC (795889HV)	
Hardness Deviation	Max Deviation $\pm 3.0$ HRC, $\pm 40$ HV	
Type	G10 G12 G14 G16 G18 G25 G40 G50 G80 G120	
Diameter	2.5mm 2.0mm 1.7mm 1.4mm 1.2mm 1.0mm 0.7mm 0.4mm 0.3mm 0.2mm	
Microstructure	Even tempered martensite and dispersed carbon	
Quality Standard	SAE, ISO9001	
Durability	?3000 times	
Shape	Angular	

### Application

- pre-coat surface preparation
- sand and rust removal
- descaling
- etching
- cleaning
- gang-saw stone cutting

### Our services

**Free samples:** We can offer you free samples to test before placing order.

**Customized services?**

Mixture of different blasting media: We can pack with different blasting media as requested.

Customized packing: Other packing style can be done according to customer' requirement.

**Technical services:**

A.Providing all-around technical support and after-sale services for customer.

B.Help to test the products for customer,which is not produced by us.

**Undertaking service:**undertaking cleaning project of casting,help customers to control blasting cost.