

3.85g /cm³ Fused Alumina, Refractory Material Brown Fused Alumina For Industry

Specifications :

Price	Contact Us
Place of Origin	Shandong, China
Payment Terms	T/T, L/C, Western Union, etc.
Delivery Detail	10-25 Working Days.
Keyword	Brown Alumina

Detail Introduction :

Brown Fused Alumina (For Refractory and Abrasive using).

Brown Fused Alumina is fusing under the high temperature of above 2250°C with high quality abrasive bauxite as raw material. It is characterized by good self-sharpening and high grinding ability. Brown Fused Alumina can produce ceramic grinding wheel, resinoid grinding wheel. And BFA could be used for abrasive, sandblasting and precision casting.

Specification:

Purpose	Size		Chemical Composition(%)				Magnetic%
			Al ₂ O ₃	Fe ₂ O ₃	SiO ₂	TiO ₂	
For Abrasive	F	4#-80#	≥95	≤0.3	≤1	≤3.0	≤0.05
		90#-150#	≥94	≤0.3	≤1	≤3.0	≤0.03
		180#-240#	≥93	≤0.3	≤1.5	≤3.5	≤0.02
	P	8#-80#	≥95.0	≤0.2	≤1.2	≤3.0	≤0.05
		100#-150#	≥94.0	≤0.2	≤1.2	≤3.0	≤0.03
		180#-220#	≥93.0	≤0.3	≤1.5	≤3.5	≤0.02
For Refractory	0-1, 1-3, 3-5, 5-8		≥95	≤0.3	≤1	≤3.0	-
	200-0, 325-0		≥94.5	≤0.5	≤1.5	≤3.5	-

Note: Size as per customer's requirement.

Packing: 1 MT big bag or 25kg paper bag on one pallet; As per customer's requirement