

Customer Size High Hardness White Fused Alumina (For Refractory And Abrasive Using)

Specifications :

Price	Contact Us
Place of Origin	Shandong, China
Payment Terms	T/T, L/C, Western Union, etc.
Delivery Detail	10-25 Working Days.
Keyword	White Fused Alumina Powder

Detail Introduction :

White Fused Alumina (For Refractory and Abrasive using)

White fused alumina electrically fused in electric furnace with high grade processed alumina as raw material. It has higher hardness and slight lower toughness comparing with brown fused alumina. It is also characterized by its high purity, ability of self-sharpening, better cutting, less heat emits, higher efficiency.

Specification:

	Size		Chemical Composition(%)			
			Al ₂ O ₃	Na ₂ O	SiO ₂	Fe ₂ O ₃
For Abrasive	F	12#-80#	>99.2	<0.4	<0.1	<0.1
		90#-150#	>99.0	<0.4		<0.1
		180#-240#	>99.0	<0.4		<0.1
	Size		Chemical Composition(%)			
			Al ₂ O ₃	Na ₂ O	SiO ₂	Fe ₂ O ₃
For Refractory	Size Sand	0-1mm 1-3mm 3-5mm 5-8mm	>99.2	<0.4 or <0.3 or <0.2	<0.1	<0.1
		Fine Powder	200-0 325-0	>99.0		<0.1

Note:Size as per customer's requirement.

Packing: 1 MT big bag or 25kg paper bag on one pallet; As per customer's requirement.