

gl40 steel grit steel grit blasting media

Specifications :

Price	Contact Us
Model Number	gl40 steel grit
Place of Origin	Shandong, China
Payment Terms	T/T, L/C, Western Union, etc.
Delivery Detail	10-25 Working Days.
Keyword	Steel Grit Abrasive

Detail Introduction :

Application:

Steel grit Blasting Cleaning

Steel shot and grit are used in cleaning applications for removal of loose material on metal surfaces. This type of cleaning is common in automotive industry.

Specifications

Product Name	Chemical Composition	
Chemical Composition	C	0.70-1.20%
	Cr	0.26%
	Mn	0.6-1.20%
	Si	0.40-1.20%
	S	≤0.05%
	P	≤0.05%
Micro Hardness	GP:4250HRC (399509HV) GL:5660HRC (620713HV) GH:6366HRC (795889HV)	
Hardness Deviation	Max Deviation ±3.0HRC, ±40HV	
Type	G10 G12 G14 G16 G18 G25 G40 G50 G80 G120	
Diameter	2.5mm 2.0mm 1.7mm 1.4mm 1.2mm 1.0mm 0.7mm 0.4mm 0.3mm 0.2mm	
Microstructure	Even tempered martensite and dispersed carbon	
Quality Standard	SAE, ISO9001	
Durability	≥3000 times	
Shape	Angular	

After-sales Service:

Our products passed ISO9001 standard, and we control the testing procedure strictly.

From the raw materials adopting to the transport to port, our staffs do their works seriously all the time. If there are quantity problems, package problems, delivery problems, or any other problems, our company will seriously investigate the event and give customers a satisfying reply.