

s280 steel shot 0.8mm for descaling

Specifications :

Price	Contact Us
Model Number	s280
Place of Origin	Shandong, China
Payment Terms	T/T, L/C, Western Union, etc.
Delivery Detail	10-25 Working Days.

Detail Introduction :

Specification

Applications: Blasting Cleaning of die casting, forgings sand removal, foundry pieces, Rust Removal of forgings, steel material, foundry pieces, steel board, Shot Blasting of steel board, profile steel, ship board, steel material, Shot Polishing of profile steel, steel board, and steel material, Shot Peening of heat treatment pieces, gears, etc, Pre-treatment of surface steel structure (before painting)

Products		Steel Shot
chemical composition	C	0.70~1.20%
	Mn	0.35~1.20%
	Si	0.40~1.20%
	S	≤0.05%
	P	≤0.05%
Microhardness		Normal:40~50HRC (377~509HV)
		Special:52~56HRC (543~620HV)
		Special:56~60HRC (620~713HV)
Hardness Deviation		Max Deviation ±3.0HRC
Microstructure		Tempered Martensite or Sorbite
Density		7.2g/cm3

Packing of Steel shot : Can also be customized according to customer requirements

- 1.25kg/bag, 40bags/pallet
- 2.25kg/bag, 40bags/MT bag
- 3.25kg/bag, 40bags/carton box
- 4.1000kgs/MT bag
- 5.900kgs/steel drum