

conditioned cut wire shot

Specifications :

Price	Contact Us
Place of Origin	Shandong, China
Payment Terms	T/T, L/C, Western Union, etc.
Delivery Detail	10-25 Working Days.
Keyword	Cut Wire Shot

Detail Introduction :

Product parameters

Produced by adopting the Drawing into wire, cutting, screen and other refined procedures. Appearance is bright, no rust, cylindrical shape (as cut).

Widely used for cleaning, deburring, surface improvement, shot blasting, shot peening of Aluminium, Non Ferrous Metals, Zinc Alloys, Stainless Steel precision etc.

Available Grades :

SUS 304

SUS 302

SUS 430

SUS 410 etc.

Hardness Range HRC : 30-40, 40-45, 45-50, 50-55

Available Sizes in mm : 0.3, 0.4, 0.5, 0.6, 0.8, 1.00, 1.2, 1.4, 1.5, 2.0, 2.5 mm

Different levels of conditioning.

CW - As Cut

G1 - Single Conditioned

G2 - Double conditioned

G3 - Spherically conditioned

Chemical composition:

Product	Grade	Hardness	Composition (%)					Density
			C	Si	Mn	Ni	Cr	
stainless steel cut wire shot	(SUS304)Austenite	300-600HV	0.08% max	1.0% max	2.0% max	8.0-10.0%	17-19	7.8g/cm ³
stainless steel cut wire shot	(SUS302)Austenite		0.08% max	1.0% max	2.0% max	4.0-6.0%	16-18	

stainless steel cut wire shot	(SUS430) Ferrite	0.12% max	0.75% max	1.2%	/	16-18
stainless steel cut wire shot	(SUS410) Martensite	0.10%	1.0% max	1.2%	/	11-13

Abrasive products	Advantage
Steel cut wire shot	High quality control,best price offer
Steel shot	Sufficient stock, Delivery timely 10-25 days
Steel grit	GE Stabilized supplier
Stainless steel shot	SAE standard, ISO9001 certificate
Cu /Al / Zn / shot etc	Flexibility &Professional customer service× 24h